

Clack® 

WS1.25EE

WATER SPECIALIST CONTROL VALVE



shown with optional bypass



Certified to NSF/ANSI 44, 61 and 372.

- Solid state microprocessor with easy access front panel settings
- Service flow rate of 34 gpm, backwash 32 gpm
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with an 8 hour carry over
- Backwash and brining ability to 21" diameter tanks
- Downflow or upflow brining regeneration
- Level VI 15-volt output DC power supply provides safe and easy installation
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Control valve design provides optimum service and backwash rates
- Post treated water regenerant refill
- Reliable and proven DC drive

Water Specialist 1.25" EE Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.5" NPS
Cycles	up to 6
Valve Material	Noryl (1) or equivalent
Regeneration	Downflow

FLOW RATES

Service @15 psi drop (includes bypass and meter)	34 gpm
Backwash @ 25 psi drop (includes bypass)	32 gpm (2)
Cv Service	8.8
Cv Backwash	6.4

OPERATING PRESSURES

Minimum/Maximum	20 psi – 125 psi
-----------------------	------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° – 110° F
-----------------------	--------------

METER

Accuracy	± 5%
Flow Rate Range.....	0.25 – 34 gpm
Gallon Range.....	20 – 1,500,000 gallons
Totalizer	1000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot.....	1.32" OD Pipe (1" NPS) or 32mm OD
Drain Line	¾" or 1" Male NPT
Brine Line	¾" or ½" OD Poly Tube Compression
Mounting Base.....	2 ½" - 8 NPSM
Height From Top Of Tank.....	7 ¾"
Weight	4.5 lbs.

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage	100VAC to 120VAC.....	200VAC to 240VAC
Supply Frequency	50/60 Hz.....	50/60 Hz
Output Voltage	15VDC.....	15VDC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener	6" – 21" diameter
Water Filter (3).....	6" – 24" diameter

CYCLES OF OPERATION

Cycle	<u>Softener</u>	<u>Filter</u>
	Range of time in minutes	
1. Backwash 1 st (upflow)	1-95.....	Backwash 1-95
2. Regenerate Draw/Slow Rinse (downflow)	1-180	
3. Backwash 2 nd (upflow).....	1-95	
4. Fast Rinse (downflow)	1-95.....	Rinse 1-95
5. Regenerant Refill (in service with treated water).....	0.1-99.0 or off	
6. Service (downflow)		

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of Sabic Innovative Plastics IP B.V. Company
2. Acquired by use of external drain line flow control
3. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area