



AM 125 SERIES

MAKING WATER SOFT FOR OVER 40 YEARS

THE AUTOMATIC WATER CONDITIONER THAT GIVES YOU MORE!

AM 125 Series



- 1 1/4" Control - Ideal for large residential/light commercial applications requiring up to 35 GPM
- Three modes of operation: meter immediate, meter delayed or time clock delayed
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, volume remaining, current flow rate and total volume used (totalizer)
- Multiple programming options, powerful, reliable and user-friendly electronics automatically monitor water-treatment functions including:
 - Days since last regeneration
 - Gallons since last regeneration
 - Number of days in service since start up
 - Total number of regenerations
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow bringing/slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with an 8 hour carry over



| Models | AM 125-48 | AM 125-60 | AM 125-75 | AM 125-90 | AM 125-120 | AM 125-150 |
|---|--------------------|------------------|------------------|------------------|-------------------|-------------------|
| Exchange Capacity Per Tank Grain @ lb. Salt | Min. 30,000 @ 9 | Min. 40,000 @ 12 | Min. 50,000 @ 15 | Min. 60,000 @ 18 | Min. 80,000 @ 24 | Min. 100,000 @ 30 |
| | Med. 36,000 @ 13.5 | Med. 48,000 @ 16 | Med. 60,000 @ 20 | Med. 72,000 @ 24 | Med. 96,000 @ 32 | Med. 120,000 @ 40 |
| | Max. 45,000 @ 22.5 | Max. 60,000 @ 30 | Max. 75,000 @ 38 | Max. 90,000 @ 45 | Max. 120,000 @ 60 | Max. 150,000 @ 75 |
| Resin (Cu Ft) | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0 |
| Mineral Tank Size (inches) | 10" x 54" | 12" x 52" | 13" x 54" | 14" x 65" | 16" x 65" | 18" x 65" |
| Brine Tank Size (in.) Salt Storage (lbs.) | 18" x 33" 300 | 18" x 40" 450 | 18" x 40" 450 | 24" x 41" 550 | 24" x 41" 550 | 24" x 50" 550 |
| Pipe Size | 1 1/4" | 1 1/4" | 1 1/4" | 1 1/4" | 1 1/4" | 1 1/4" |
| Flow Rate (Cont. 15 psi) (Peak 25 psi) | 19 28 | 23 31 | 24 32 | 24 33 | 25 34 | 27 35 |
| Backwash Rate | 2.2 gpm | 3.2 gpm | 4.2 gpm | 5.3 gpm | 6.5 gpm | 7.5 gpm |

SOLD BY:

Products of

