



GUARDIAN SERIES

- Protects appliances and fixtures from staining
- Safe - No Chemicals
- Low cost - Requires only periodic backwashing
- No Filters to change
- Long material life expectancy
- High iron removal efficiency
- Reduces hydrogen sulfide (rotten egg odor)*

* Use Guardian Carbon or Guardian O₂/Carbon for this application



****PUMP OUTPUT MUST MATCH OR EXCEED BACKWASH RATE**

	Tank Size (inches)	Media (cu.ft.)	Media Type	Backwash Flow Rate (gpm)	Service Flow Rate (gpm)
Guardian	10 x 54	1.5	Clinoptilolite	7.5	2.75
Guardian O ₂	10 x 54	1.5	O ₂ Catalytic	5.3	2.75
Guardian Carbon	10 x 54	1.5	Cat Carbon	5.3	2.75
Guardian O ₂ /Carbon	10 x 54	1.5	O ₂ Cat/Carbon	5.3	2.75

**Guardian Series not to be used with microbiologically unsafe water sources

**Free chlorine concentration less than 0.5ppm and PH range of 6.8-9.0 is required for Guardian O₂ and Guardian O₂/Carbon systems

**Guardian Series available in 1.25", 1.5", and 2" systems

SOLD BY:

