

Darrington

WATER • CONDITIONING

Mur-lok RO fittings are the only RO fittings that feature dual EPDM O-rings to ensure a straight leak free fit. These high-quality American made fittings are constructed with FDA approved materials. Polypropylene construction NSF Standard 58 Certified Sizes Available. We carry various sizes (1/4" – 3/8" – 5/16") for all fittings listed below and mixed sizes . Just give us a call for sizing and fitment. More products are available, let us know what you need and we will help you get the right part for your job.



Mur-Lok
FEMALE NPT PUSH CONNECT



Mur-Lok
REDUCING UNION PUSH CONNECT



Mur-Lok
EZ FAUCET ADAPTER



G.A. Murdock
NPT PUSH CONNECT ELBOW BALL VALVE



Mur-Lok
TEE PUSH CONNECT



Mur-Lok
RO STRAIGHT UNION PUSH CONNECT



Mur-Lok
RO ELBOW - MALE NPT X PUSH CONNECT



Mur-Lok
RO ELBOW UNION PUSH CONNECT



Mur-Lok
MALE NPT X PUSH CONNECT



Mur-Lok
RO INLINE BALL VALVE PUSH CONNECT



Mur-Lok
INLINE CHECK VALVE PUSH CONNECT



Mur-Lok
EZ FAUCET ADAPTER KIT



Mur-Lok
RO TEE UNION PUSH CONNECT



Mur-Lok
RO ELBOW - STEM X PUSH CONNECT



Mur-Lok
RO TUBE DIVIDER PUSH CONNECT



Mur-Lok
FAUCET / REFRIGERATOR ADAPTER PUSH CONNECT



Make quick work of push connect fittings!
The Mur-Lok Fitting Release Tool works with all types of push connect fittings that are commonly used with RODI systems and reactors.

If you ever work with push connect fittings you may find that pushing the small collet into the fitting while pulling the tube can be a challenge sometimes, especially in tight places. The Mur-Lok Fitting Release Tool will let you disconnect the fittings while keeping your finger tips from getting sore (these are especially valuable if you have a lot of fittings to go through).

Using the release tool is super simple, just place the properly sized shoe around the tubing and push it down into the fitting, depressing the collet. Then while you are pushing the collet into the fitting, pull the tubing out of the fitting and you are done!

Works with:

- 1/4" Push Connect Fittings
 - 3/8" Push Connect Fittings
 - 1/2" Push Connect Fittings
-



Mur-Lok
3/8" or 1/4" POLYETHYLENE RO TUBING

Made in the USA, Mur-lok Linear Low-Density Polyethylene (LLDPE) tubing is designed for use with all Mur-lok and John Guest push connect fittings. Mur-lok polyethylene tubing offers excellent pressure and temperature ratings and has outstanding resistance to environmental stress cracking, surpassing 1000 hours of ASTM D1693 (10% IGEPAL testing). The tubing is BPA-Free, FDA approved materials and is NSF Standard 58 Certified.

The Mur-lok LLDPE Tubing is NSF 58 Component Certified. The products were put through rigorous structural and material testing to help ensure they meet the standards for drinking water. This certification also ensures that Mur-lok tubing can be easily incorporated into any NSF certified drinking water system with minimal paperwork and minimal, if any, re-testing.